# G50-100 Polyethylene Copolymer

G50-100 is a high molecular weight, high density polyethylene copolymer developed for sheet extrusion, thermoforming and large part blow molding where the finished product demands outstanding physical performance. This material meets the Food and Drug Administration requirements of 21CFR 177.1520.

### Typical Properties<sup>1</sup>

	Values		ASTM Method
	<b>English Units</b>	SI Units	
Density	_	0.950  g/cc	D 4883
Melt Index <sup>2</sup>	_	10.0  g/10  min	D 1238
Tensile Strength		C	
@ Yield (2 in/min)	3800 psi	26.2 MPa	D 638
@ Break (2 in/min)	4400 psi	30.3 MPa	D 638
Elongation	-		
@ Break (2 in/min)	>800%	>800%	D 638
Tensile Modulus of Elasticity <sup>3</sup>	180,000 psi	1241 MPa	D 638
Flexural Modulus <sup>3</sup>	175,000 psi	1205 MPa	D 790
Tensile Impact <sup>4</sup>	$250 \text{ ft-lb/in}^2$	$525 \text{ kJ/m}^2$	D 1822
Hardness (Shore D)	65	65	D 2240
Vicat Softening Point	266 °F	130 °C	D 1525
Brittleness Temperature	<-103 °F	<-75 °C	D 746
Deflection Temperature @ 66 psi	158 °F	70 °C	D 648
Coefficient of Linear			
Thermal Expansion	0.00007 in/in/°F	$0.00012~\mathrm{cm/cm/^{\circ}C}$	D 696

<sup>&</sup>lt;sup>1</sup> Typical properties will vary within specification limits. <sup>2</sup> 190° C/21600 g

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of the this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices, or from hazards inherent in the nature of the product and/or material, nor for toxicological effects or Industrial Hygiene associated with particular use of any product described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material or in any process, unless otherwise specified. This information shall not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.



<sup>&</sup>lt;sup>3</sup> Tangent-Method <sup>4</sup> Type L

## G50-100 Polyethylene Copolymer

#### **Regulatory Information**

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, please refer to the Regulatory Position Statement (RPS) online at <a href="https://www.ineos-op.com">www.ineos-op.com</a>, or call + 1-800-527-5419.

#### Health and Safety Information

The product described herein may require precautions in handling and use because of toxicity, flammability, or other consideration. The Material Safety Data Sheet (MSDS) contains the available product health and safety information for this material and can be found at **www.ineos-op.com**. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

The Material Safety Data Sheet for this product contains shipping descriptions and should be consulted, before transportation, as a reference in determining the proper shipping description. If the material shipped by INEOS O&P is altered or modified, different shipping descriptions may apply and the MSDS of the original material should not be used.

For additional information, samples, pricing and availability, please contact:

#### INEOS Olefins & Polymers, USA

Marina View Building 2600 South Shore Boulevard Suite 500 League City, Texas 77573

Phone: +1 281 535 6600 Fax: +1 281 535 6764

Customer Service: +1 800 527 5419 Tech Service: +1 800 338 0489

www.ineos-op.com

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of the this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices, or from hazards inherent in the nature of the product and/or material, nor for toxicological effects or Industrial Hygiene associated with particular use of any product described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material or in any process, unless otherwise specified. This information shall not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.

