



Snetor

HD-5502

HIGH DENSITY POLYETHYLENE BLOW MOLDING

Technical Data Sheet

HD-5502 is a Blow Molding Grade that provides good impact strength and stress crack resistance.

Applications include oil bottles, household/ industrial containers, toys and personal care products.

NOMINAL RESIN PROPERTIES	NOMINAL VALUE (ENGLISH)	NOMINAL VALUE (SI)	METHOD
Density	0.955	g/cm ³	ASTM D792
Melt Index, 190C/2.16Kg	0.35	g/10min	ASTM D1238
Tensile Strength @ Yield	4.000	Psi	ASTM D638
Elongation @ Break	600	%	ASTM D638
Flexural Modulus	200.000	Psi	ASTM D790
Melting Temperature	264	°F	ASTM D3417



One River Way, Ste 1125 –
Houston, TX, 77056 - USA
Email: plastics@snetor.fr



Tel : +33 1 49 04 88 88
Email: plastics@snetor.fr

Disclaimer :

The information on this document is, to our knowledge, true and accurate. Due to operating conditions and intended uses beyond our control, it is the customer's responsibility to establish satisfactory performance of this product for the intended application. By providing the information contained herein, SNETOR, makes no guaranty or warranty, and does not assume any liability with respect to the completeness of such information.